

## **Salamander Custom In-Cabinet Leon Speakers**

Salamander's speaker integrated cabinets feature quality craftsmanship and high-fidelity sound by Leon Speakers. Each speaker is handcrafted and built-to-order to **fit seamlessly into our Synergy and Chameleon AV cabinets**. Each speaker features world-class Peerless woofers and cloth-dome tweeters, creating a high-fidelity system with exceptional sonic clarity. Designed to achieve maximum performance, our speaker integrated cabinets will transform any home theater setup into a cinematic experience with truly captivating audio capabilities.

Custom built to seamlessly integrate with our Synergy and Chameleon AV cabinets Exclusive mounting brackets allow for articulation to optimize sound dispersion High-peformance sound platform features world-class woofers and cloth-dome tweeters for exceptional sonic clarity Solid MDF construction, meticulously crafted by hand in the USA

8" Cente	er Channel	Soundbar / LCR (left-center-right)		
(SD/SPK1/C - fits C	9 3/8" hameleon Single-Width Bays) ynergy Single-Width Bays)	40 1/8"w - (SI 60 7/8"w - (SI	D/SPK2/C, fits Chameleon Twin- D/SPK2/S, fits Synergy Twin-Wid D/SPK3/C fits Chameleon Triple- D/SPK3/S fits Synergy Triple-Wid	th Bays); Width Bays);
Components	5" midrange woofers; 1"audiophile-grade tweeters		Center Channel	LCR (left-center-right) Speaker
Model	SD/SPK1/C, SD/SPK1/S, SD/SPK2/C, SD/SPK2/S, SD/SPK3/C, SD/SPK3/S	Impedance	8Ω	6Ω
Height	8"	Rec. Power	50–250W	50–250W
Width	Varies, depending on model	Maximum Output	104 dB avg; 110 dB peak	101 dB avg; 107 dB peak
Depth	4"	Coverage	Hor: 110°; Vert: 140°	Hor: 110°; Vert: 140°
Material	Sealed MDF enclosure	Freq. Response	74–22kHz (+/- 3dB)	74–22kHz (+/- 3dB)
Weight	15-30 lbs (depending on configuration and width)	Sensitivity	88dB@2.83V/1m	88dB@2.83V/1m
Finish	Matte black	Connections	5-way binding post	